

CMCM2FB - NUC Pro with AV Chassis

Modular Customization

Intel® NUC Elements are an entirely new way to design and build Mini PCs. Compute module options along with a series of Intel-designed components, deliver the flexibility of modular computing letting you create the exact systems you want. Intel NUC Elements include compute module and chassis module options, allowing you to develop innovative solutions. Start with a compute module with the exact processor you need and plug it into your choice of chassis module. By transforming how systems can be built and serviced, Intel is once again revolutionizing computing in order to help you succeed. Perfect for many uses from Telehealth to conferencing, even work from home. The Intel NUC Elements let you deliver custom solutions with minimal R&D time.

Audio Video Features

Fort Beach is available in two options CMCM2FB and the AV optioned CMCM2FBAV. The Video Capture and Audio version features an internal HDMI video capture card with up to 1080P resolution, HDMI passthrough and audio in/out for a I/O-rich solution to capture, stream and record. Compact and powerful, the Intel NUC Compute Element along with Intel NUC Board and Chassis Elements, deliver the flexibility of modular computing—so you can create custom solutions to fit your clients' exact needs.

Build Embedded Solutions

Intel® NUC Elements enable you to design systems for video collaboration, distance learning, and other A/V based deployments. Housed in a small quiet chassis that will fit almost anywhere. The NUC 8 Pro can be easily integrated into digital solutions. The two chassis options provide flexibility in usage, and are qualified for 24/7 operation, making it the ideal PC solution for virtual meetings, live streaming workshops and recasting presentations. All modules carry a 3-year warranty, for performance that's designed to last.

Highlighted features

- Intel® NUC Compute Module U-Series (Required)
- Actively-Cooled chassis
- Dual M.2 slots for NVMe and SATA SSDs
- Intel® Optane™ Memory ready
- Dual HDMI 2.0a for dual 4K@60Hz
- Dual Intel® Gigabit LAN
- 3x USB 3.1 gen 2 type A ports
- 1x front port & 2x internal USB 2.0 type A
- Up to 7.1 multichannel (or dual 8-channel) digital audio via HDMI
- Front panel header with Vcc5/1A, 5Vsby2A, 3.3Vsby1A
- Qualified for 24x7 operation; delayed AC start; DC overvoltage protection
- EDID emulation
- RP-SMA Dual-Band Antennas
- 12 – 24V_{DC} rear jack
- Metal chassis with Kensington lock
- VESA plate included
- Internal Wi-Fi and Bluetooth antennas

Customization

- Intel® NUC Compute Module U-Series
- Dual M.2 SSDs 128GB-4TB Max, Select Processors 64GB eMMC Storage
- Two Models: Base (CMCM2FB) / Video Capture Audio (CMCM2FBAV)



Front: CMCM2FB and CMCM2FBAV



Back: CMCM2FB: Base



Back: CMCM2FBAV: Video Capture Audio

Simply NUC Services

You can order this NUC in your various configurations, as well as your corporate OS Image loaded and ready to deploy.

Chassis Technical Specifications

Storage Capabilities

- One M.2 22x80 key M slot for PCIe x4 NVMe or SATA SSDs
- One M.2 22x80 key M slot for SATA SSDs
- Intel® Optane™ Memory H10 With Solid State Storage ready

Audio

- Up to 7.1 multichannel (or dual 8-channel) digital audio via HDMI

Hardware Management Features

- Trusted Platform Module (TPM) 2.0
- AMT supported Ethernet Controller
- Voltage and temperature sensing
- ACPI-compliant power management control

Peripheral Connectivity

- Intel® UHD Graphics 620 (Intel® Core™ processors) or Intel® UHD Graphics 610
- Intel® i219-LM 10/100/1000 Mbps RJ45 Ethernet; 2nd Intel® i211-AT 10/100/1000 Mbps RJ45 Ethernet
- Three USB 3.1 gen 2 type A ports (one front panel port and two back panel ports)
- Three USB 2.0 type A ports (one front panel port and two back panel ports)
- Display Emulation (headless display, virtual display, persistent displays)

Video Ports

- Two HDMI 2.0a ports with CEC support for dual 4K@60Hz

Front Panel Header

- Front panel header (with Vcc5/1A, 5Vsby2A, 3.3Vsby/1A)

CMCM2FBAV Additional Features

- HDMI Video Capture up to 1080p with HDMI Passthrough
- 3.5mm Audio In and Out jacks

Baseboard Power Requirements

- 19V, 90W AC-DC power adapter with detachable power cord.
- Includes geo-specific AC cords (IEC C5 connector)

Mechanical Chassis Information

- 7.9" x 5.9" x 1.4" (200 x 150 x 36 mm, (plus rubber feet height)
- VESA Mount Kit (Plate and Screws) mechanical support for power supply adapter
- 1.9kg (4.2lbs) Fully-Assembled with Antennas (no power adapter)

Certification and Regulations

Product Safety Regulations and Standards

- IEC/EN/UL 60950-1
- IEC/EN/UL 62368-1

EMC/RF Regulations and Standards (Class B)

- FCC Part 15B
- CISPR/EN 55032/55024
- ICES-003
- VCCI 32
- BSMI CNS 13438
- KN 32/35
- AS/NZS CISPR 32
- EN 300 328
- EN 301 893
- EN 300 440
- EN 301 489-1/3/17
- EN 62311
- AS/NZS 4268
- AS/NZS 2772.2
- ARPANSA

Environmental Regulations

- EU RoHS
- China RoHS
- Taiwan BSMI RoHS
- REACH

Environment Operating Temp

- 0° C to +35° C
- Non-condensing Humidity

Storage Temperature

- -20° C to +70° C

Certified Operating Systems

- Windows 10 64-bit (Pro & Home)
- Windows 10 IoT Enterprise - (64-bit only) CBB and LTSB
- Windows Server 2016
- Various Linux including: (Contact Simply NUC for specifics)